

Standard Wood Veneer Doors

CENDURA® SERIES

Fire-Resistant Mineral Core 45-90 Min / Bonded Construction Wood Veneer

FORTE
OPENING SOLUTIONS

	Models	C-MC-B-FR45 C-MC-B-FR60 C-MC-B-FR90			
DIMENSIONS	Thickness	1-3/4"			
	Maximum Size	ITS-WH and UL Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.			
			Neutral Pressure	CAT A Positive Pressure	CAT B Positive Pressure
		Singles	4'0"x9'0"	4'0"x9'0"	4'0"x9'0"
		Pairs	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"
		DE Pairs	8'0"x8'0"	8'0"x8'0"	8'0"x8'0"
CONSTRUCTION	Surface Material	Wood Veneer: A Grade Only-Book and Running Match. Non-figured veneer only. Rotary and Plain Sliced: Natural Birch, White Birch, White Oak (Plain Sliced Only), Red Oak, White Maple, Natural Maple (excludes bird's eye) Rift Cut-Slip Match: Red Oak, White Oak			
	Crossbands	One Piece High-Density Fiberboard (HDF)			
	Vertical Edges*	Hardwood Composite Fire Stile			
	Horizontal Edges*	Manufacturer's standard construction per label service listing			
	Face/Core Assembly Adhesive	Type 1			
	Core Construction	Mineral Core			
	Lite Openings/Louvers	- Factory glazing recommended – max 5/16" glass thickness - Standard veneer wrap bead, standard metal vision frames - Standard fusible link door louver - Standard applied grilles			
	Distance from Lock and Lite Cutouts	3-1/4" minimum distance from adjacent lock and lite cutouts			
	Details	Standard and custom applied moulding profiles			
	Machining	Machining preparation per hardware manufacturer's templates. Some limitations apply.			
	Factory Finish	- Meets WDMA TR-8 and AWS System 12 - Clear, standard and custom stain colors			
STC	Acoustic Rating†	STC 30 Operable when installed with tested seals and gaskets - Refer to Appendix M			
CREDITS & STANDARDS	Environmental Options	- CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request			
	Environmental Product Declaration	Yes			
	Quality Standards	- WDMA I.S.1A Architectural Wood Flush Doors (Standard Construction)			
WT.	Door Weight	Thickness	lbs/sf		
		1-3/4"	3.7		
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.			

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

* Fire-Rated doors will be constructed per label service listing and may deviate from above.

† Performance Duty Level and STC Ratings are based on 1-3/4" doors.

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde) Refer to Tech Bulletin 139.