D2 SERIES HEAVY DUTY DEADBOLT



2" ADA Approved Thumb Turn with 3/32" Steel Mounting plate







Specification

ANSI: Meets & Exceeds ANSI - A 156.2, Grade 2 Standards

UL Listings: UL Listed for "A" Label 3 Hour Fire Doors

ADA Compliance: 2" ADA Thumbturn Meets ADA & ANSI A117. 1 accessibility codes

Lock Chassis: Steel, Zinc dichromated for corrosion resistance

Trim: Free spinning cylinder collar resists wrenching and prying

Handing: Non-handed - Completely reversible

Backset & Latchface: 23/4" fixed backset std. with 11/8" x 21/4" latchface, 23/8" backset available with 1" x

2 1/4" latchface both with self adjusting front for square or beveled doors

Latchbolt: Grade 1 Solid Brass with 1" Throw & Anti-Saw Hardened Steel Pin Insert

Cylinder Options: 6 Pin Brass, C Kwy, with 2 Keys std, Prepared for Small format IC core (less core)

Strike: $11/8" \times 23/4"$ Square corner

Door Preparation: ANSI A115.2 - 21/8" crossbore

Door Thickness: 13/4" thick doors

Standard Finishes: US3 PVD*, US4, US10B, US15, US19, US26 PVD*, US26D (PVD = Lifetime Finish)

Fasteners: Combination screws for wood or metal doors & frames

Warranty: Limited lifetime warranty



