

Forte **CENDURA™ SERIES | MOHAWK®** - Distributed by Trudoor

Particleboard Core Non-Rated & 20 Min / Bonded Construction Wood Veneer

Models		C-PC-B-NR C-PC-B-FR20			
DIMENSIONS	Thickness	1-3/8", 1-3/4"			
	Maximum Size	ITS-WH and UL- Max 20 Minute Sizes noted in this table are specific to 1-3/4" doors. Contact sales for information regarding other door thickness types.			
			Non-Rated	Neutral Pressure	CAT A Positive Pressure
		Singles	4'0"x9'0"	4'0"x9'0"	N/A
		Pairs	8'0"x9'0"	8'0"x9'0"	8'0"x9'0"
CONSTRUCTION	Surface Material	Wood Veneer: A Grade Only-Book & Running Match. Non-figured veneer only. Rotary and Plain Sliced: Natural Birch, White Birch, White Oak (Plain Sliced only), Red Oak, White Maple, Natural Maple (excludes bird's eye) Rift Cut-Slip Match: Red Oak, White Oak			
		One Piece High Density Fiberboard (HDF)			
	Crossbands	Default: Full Length Mill Option Softwood/Mill Option Low Density Hardwood Alternate Stile Options Upon Request: Full Length Mill Option Low Density Hardwood (1.281 before trim)			
	Vertical Edges*	Default: Structural Composite Lumber (1-1/4" before trim) Alternate Rail Options Upon Request: -Wide rails			
	Horizontal Edges*	Type 1			
	Face & Core Assembly Adhesive	Wood-based particleboard core			
	Core Construction	- Factory glazing recommended-max 5/16" glass - Available with standard profile wood beads, standard metal vision frames, or standard applied grilles - Standard wood and metal louvers-non-rated doors only			
	Lite Openings / Louvers	3-1/4" minimum distance from adjacent lock and lite cutouts			
	Distance from Lock & Lite Cutouts	Standard and custom profiles of applied moulding			
	Details	Machining preparation per hardware manufacturer's templates			
STC	Acoustic Rating†	STC 30 Operable when installed with tested seals and gaskets - Refer to Appendix M			
	Environmental Options	- CARB PH2/TSCA Title VI Compliant - ULEF/NAUF* upon request - FSC upon request			
	Environmental Product Declaration	Yes			
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)			
CREDITS & STANDARDS	WDMA Performance Duty Level†	Heavy Duty Note: This construction meets Extra Heavy Duty face screw pull values when surface mounted hardware is attached with through-bolts.			
	Door Weight	Thickness	lbs/sf	Thickness	lbs/sf
		1-3/8"	4.3	1-3/4"	5.5
WT.	Warranty	Limited Lifetime. No exterior warranty. Interior use only.			

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

* Fire-Rated doors will be constructed per label service listing and may deviate from above.

† Performance Duty Level and STC Ratings are based on 1-3/4" doors.

Forte Architectural Doors Distributed by Trudoor

www.trudoor.com

*As of 2018, NAUF is no longer recognized by California Air Resources Board (CARB). CARB has instead opted for ULEF (Ultra Low Emitting Formaldehyde) or NAF (No Added Formaldehyde)
Refer to Tech Bulletin 139.