

HP90-FB

Flush Bolt Hardware Prep Filler

PRODUCT CUT SHEET

UL Certified Solution for Fire Doors When Either Removing Existing Hardware and/or Using a New Hardware Type Over Existing Hardware Prep's







- Application Certified on Both Hollow Metal and Wood Fire-Rated Doors up to 90-Minute
- Patent Pending
- Certified for Filling Manual or Automatic Flush Bolt Cavities

PRODUCT CONSISTS OF:

- + HP90 2" × 6" Rectangular Fire-Rated Panel
- + HP90 0.5 Cylindrical Fire-Rated Panel
- + Steel Filler Plates: (Powder Coated Primer Gray, Embossed With UL Mark)
 - HP90-FBE6750, Edge Filler Plate
 - HP90-FBE8500, Edge Filler Plate
 - HP90-FBL2000, Latch Bolt Filler Plate
 - HP90-FBL2500, Latch Bolt Filler Plate
 - HP90-FBL3875, Latch Bolt Filler Plate
 - HP90-SF2250, Strike Filler Plate
- + Hardware Pack
 - #10-32 × 13/4" FHPH SS machine screw
 - #8 × 3/4" FHPH SS combo screw
 - #12 × 1" FHPH SS combo screw
 - #8 × 3/4" FHPH SS SMS
 - #12 × 1" FHPH SS SMS
- + GapGuard™ Fire Caulk (see Installation Instructions)
- Sizes: Flush Bolt Hardware Prep

FINISH:


Primer Gray, Powder Coat



SPECIAL NOTES:

- 90-minute rated UL Certified Miscellaneous Fire Door Accessory on UL10B and UL10C wood or hollow metal fire doors
 To retain UL Certification,
- the HP90-FB must be installed using GapGuard™ Fire Caulk





NGP-GAP-HP90-FB-PCS-0621-A

