

## Locking Devices – 2925 Electric Strike

### MODEL

2925

4-7/8" (124 mm) faceplate for aluminum, wood, and hollow metal frames

### WARRANTY

One-year warranty

### APPLICATION

- Cylindrical locksets with up to 5/8" (15mm) throw latch bolts
- Access controlled ingress for fail secure or fail safe openings (field selectable)
- Economy option provides great performance and value

### Latch

1/2" (13 mm) [5/8" (16 mm) with 1/8" (3 mm) door gap]

### FEATURES

#### Components

- Quick and easy installation with low profile 1-1/4" (32 mm) backset
- All stainless steel parts with durable diecast body for corrosion resistance
- Compact low profile design with internally mounted solenoid and factory supplied mounting tabs
- Non-handed (reversible)
- Latch status output (standard)

#### Certifications

- ANSI/BHMA A156.31, Grade 2

### ELECTRICAL SPECIFICATIONS

#### Input:

#### Current/Voltage

200/100 mA @ 12/24VDC (Field selectable)

#### Monitoring:

#### Latch Status (Std)

SPDT, DRY 3A @ 30VDC

### MECHANICAL SPECIFICATIONS

#### Dimensions

1-1/4" (32 mm) W x 4-7/8" (124 mm) H x 1-1/4" (32 mm) D

### ACCESSORIES

#### BUZZ

- Part no. 2-679-0028
- Plug-In Buzzer 12/24VDC
- Indicates fail secure strike is energized and unlocked

#### RECT

- Part no. 2-679-0029
- Converts AC to DC
- Wire leads

### FINISHES

US32D

