



## 8103EZHD Solid door pull - 1" round Large 2-1/2" clearance for the accessibility applications

Available Sizes: 8", 10", 12"

### Certifications

- Meets ANSI A156.06
- Complies with ADA and barrier free applications

### Mounting

- Heavy duty mounting hardware exceeds industry standards
- 3/8-16 mounting hardware
- Specify door thickness. Standard mounting hardware for door thickness of 1-1/2" to 1-3/4" unless otherwise specified. Optional package available for 2" and 2-1/4" thick doors.
- Comes standard with thru-bolt screws and decorative washers.
- Optional mounting hardware available (see general information section for details) A, F, I, L, N, O, P, Q, X
- Mounting hardware for other door thicknesses are available as engineering special, consult customer service.

Product number	Projection "A"	Clearance	Center to center "B"	Overall length "C"
8103EZHD-8	3-1/2"	2-1/2"	8"	9"
8103EZHD-0	3-1/2"	2-1/2"	10"	11"
8103EZHD-2	3-1/2"	2-1/2"	12"	13"

### Finishes

- Available in Aluminum, Brass, and Stainless Steel substrates. See general information section for specific BHMA finish code, finish description, US finish code, and substrate information.
- 316 Series Stainless Steel standard, exceeding industry standards for corrosion resistance. Recommended for external applications
- Standard finishes available; 605, 606, 612, 613, 619, 625, 626, 626-AM, 628, 629-316, 630-316, 630-AM, 643e/716, BLK
- Custom finishes are available as engineering special, consult customer service.

### Additional information

- Specify PR when ordering a set of pulls for back to back mounting
- For one back to back machined pull, specify Nsgl or Psgl (glass doors)
- Custom lengths are available as engineering special, consult customer service.