D1 SERIES EXTRA HEAVY DUTY DEADBOLT



2" ADA Approved Thumbturn with 1/8" Steel Mounting Plate







Specification

ANSI: Meets ANSI - A156.2, Grade 1 Standards

UL Listings: UL Listed for "A" Label 3 Hour Fire Doors

ADA Compliance: 2" ADA Thumbturn Meets ADA & ANSI A117.1 accessibility codes

Lock Chassis: Steel, Zinc dichromated for Corrosion Resistance

Steel Security Shield included to protect bolt from ice pick attack through door

Trim: Free spinning Solid Steel cylinder collar resists wrenching and prying

Handing: Non-Handed - Completely reversible

Backset & Latchface: 23/4" fixed backset std. with 11/8" $\times 21/4$ " latchface, 23/8" backset available with 1" $\times 21/4$ " latchface, 23/8" backset available with 1" $\times 21/4$ " latchface, 10 backset available with 10 backset std.

1/4" latchface both with self adjusting front for square or beveled doors

Latchbolt: Solid Brass with 1" Throw & Anti-Saw Hardened Steel Pin Insert

Cylinder Options: 6 Pin Brass, C Kwy, with 2 Keys std, Prepared for Small format IC core (less core)

Prepared for Schlage Large Format IC core (less core)

Strike: 11/8" x 23/4" Square corner, Wood Frame Reinforcer & 3" screws also included

Door Preparation: ANSI A115.2 - 2 1/8" crossbore on doors

Door Thickness: 13/4" thick doors

Standard Finishes: US3 PVD*, US10B, US15, US26 PVD*, US26D (PVD= Lifetime Finish)

Fasteners: Combination screws for wood or metal doors & frames

Warranty: Limited Lifetime Warranty



