## Five Knuckle Heavy Weight Full Mortise Series

Recommended for use on high frequency and/or heavy wood or metal doors in schools, hospitals or other public buildings where heavy traffic is experienced.

- Heavy weight hinges should be used on all extra heavy doors or those exposed to high frequency use
- T4A3386- Stainless steel base or available in brass base material polished
- T4A3786- Steel base material
- For Beveled Edge, where doors are beveled on hinge side, specify T4A4386 or T4A4786
- For available finishes see page 28

**Note:** 8" x 6" and 8" x 8" have six bearings. Specify T6B3386 or T6B3786.

No.	ANSI Cross Reference	Base Material	Weight
T4A3386	A5111	Stainless	HVY
T4A3386	A2111	Brass	HVY
T4A3786	A8111	Steel	HVY

## **Specifications**

			No. of	No. of Fasteners	
Inches	mm	Gauge	Holes	Machine	Wood
4 <sup>1</sup> / <sub>2</sub> " x 4"	114.3 x 101.6	.180	8	<sup>1</sup> / <sub>2</sub> x 12-24	11/4 x 12
4 <sup>1</sup> / <sub>2</sub> " x 4 <sup>1</sup> / <sub>2</sub> "	114.3 x 114.3	.180	8	<sup>1</sup> / <sub>2</sub> x 12-24	11/4 x 12
5" x 4 <sup>1</sup> / <sub>2</sub> "	127 x 114.3	.190	8	<sup>1</sup> / <sub>2</sub> x 12-24	11/4 x 12
5" x 5"*	127 x 127	.190	8	<sup>1</sup> / <sub>2</sub> x 12-24	1 <sup>1</sup> / <sub>4</sub> x 12
6" x 5"*	152.4 x 127	.203	10	1/2 x 1/4-20	1 <sup>1</sup> / <sub>2</sub> x 14
6" x 6"*	152.4 x 152.4	.203	10	1/2 x 1/4-20	11/2 x 14
8" x 6"**	203.2 x 125.4	.203	16	1/2 x 1/4-20	11/2 x 14
8" x 8"***	203.2 x 203.2	.203	16	1/2 x 1/4-20	11/2 x 14

<sup>\*</sup> Not available in brass base material.


McKinney is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc., an ASSA ABLOY Group company.

 $part\ without\ the\ express\ written\ permission\ of\ ASSA\ ABLOY\ Accessories\ and\ Door\ Controls\ Group,\ Inc.\ is\ prohibited.$ 

Copyright © 2012-2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in

T4A3386 T4A3786





## **Options:**

Code	Description
NRP	Non-Removable Pin
T4B	Ball Bearing
TCA	Concealed Bearing
RC	Round Corner – 1/4" radius furnished unless specified otherwise
HT	Hospital Tip
BT****	Ball Tip
FT ****	Flat Tip
ST****	Steeple Tip
SSF	Safety Stud Feature
RB	Raised Barrel*
QC	ElectroLynx® Hinge – 4, 8 or 12 wire available
СС	Concealed Circuit – 4, 8 or 12 wire available
CC-18	Concealed Circuit – 2, 4, 6, 8 or 10 wire available (2-18AWG wires and the remainder 28AWG wires)
ММ	Magnetic Monitoring

\* Refer to page SP-3 for Raised Barrel.



<sup>\*\*</sup> Available in steel only.

<sup>\*\*\*</sup>Available in stainless steel only.

<sup>\*\*\*\*</sup>FT tips not offered on 6" and 8" sizes, BT and ST not offered on 8" sizes.