

**SPECIFICATIONS:****MATERIAL:**

Steel

DESCRIPTION:Five Knuckle Heavy
Weight Hinge**FASTENERS:**

- (8) 1/2" x #12-24 Machine Screws
- (8) 1 1/4" x #12 Wood Screws

OPTIONS:

- NRP–Non-Removable Pin
- TB–Ball Bearing
- TCA–Concealed Bearing
- RC–Round Corner - 1/4" radius furnished unless specified otherwise
- HT–Hospital Tip
- BT–Ball Tip
- FT–Flat Tip
- ST–Steeple Tip
- SSF–Safety Stud Feature
- RB–Raised Barrel
- QC–4, 8, or 12 wire available
- CC–4, 8, or 12 wire available
- CC-18–2, 4, 6, 8, or 10 wire available (2-18AWG wires and the remainder 28AWG wires)
- MM–Magnetic Monitoring

SIZE:

5" x 5"

AVAILABLE FINISHES:

- US3/632
- US4/633
- US10/639
- US10A/641
- US10B/640
- US15/642
- US26/651
- US26D/652
- BSP–Black Suede Powder Coat
- WSP–White Suede Powder Coat

PACKAGED/WEIGHT:

- 3 ea Per Box
- 24 ea Per Case
- Case Weight–55 lbs

UL/ANSI:NFPA 80 UL Openings
A8111 Grade 1