Rockwood 550

Lever Extension Flush Bolt



Experience a safer and more open world





This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

SPECIFICATIONS:

MATERIAL:

Brass

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

8 ea. #8 x ³/₄" Flat Head Combo Screws

FEATURES:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
- 3/4" bolt throw, 3/4" rod backset
- 12" rod length (center of face to bolt end retracted)
- 1 1/2" adjustable bolt head

OPTIONS:

- Other size rods available are 18", 24", 36", 48"
- Use #570 Dust Proof Strike to prevent dirt blocking bottom strike

NOTE: UL Rated for use on Metal Doors only.

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26/625
- US26D/626
- BSP (Black Suede Power Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Size:

Face Plate: 1 1/4" x 6 3/4" Strike: 15/16" x 2 1/4" Guide: 1" x 2"

Weight: 1.7 lbs./2

ANSI A156.16: L04251

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424