

# Rockwood OH1003M

## Standard Duty Overhead Stop

Surface Mounted - Multi-Function - Center Hung 32 1/16" - 38"

Experience a safer  
and more open world



### SPECIFICATIONS:

**MATERIAL:**  
Stainless Steel

#### FEATURES:

- Single acting doors
- Non-handed
- Slide track design
- Recommended for medium traffic, medium weight doors
- Degree of opening fully adjustable and can be adapted to changing needs
- Heavy shock absorber spring provides compression before deadstop
- Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in field. MF5012 KIT (Adapter kit) included.
- Complete screw packet with thru-bolts for door, wood and machine screws for frame
- Torx® screws optional for security applications, but heavy-duty units should be considered for high-security applications
- Durable slider cam and shock block
- 110° maximum opening
- 3/4" square channel
- Stop function UL listed for fire door assemblies
- For pull side mounting or flush and rabbeted mounting on push side use angle jamb bracket adapter JB1000

#### FASTENERS:

Jamb: #12 x 1 1/2" Flat Head Wood Screws or #12-24 x 1/2" Flat Head Machine Screws

Door: #12-24 x 1 1/2" Flat Head Machine Screws and Ø 5/16" Sex Bolt

#### OPTIONS:

- Multi-function
- Butts/Offset Pivots  
30 1/16" - 36"
- Multi-function unit can be converted to a hold open or friction unit in the field



### AVAILABLE FINISHES:

- US32D/630
- US10BE

### WEIGHT:

3.5 lbs.

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
www.rockwoodmfg.com  
1 800 458 2424

Copyright © 2019-2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.