

# Rockwood OH903S

## Heavy Duty Overhead Stop

Surface Mounted - Stop Only Center Hung 36 1/16" - 41"

Experience a safer  
and more open world



### SPECIFICATIONS:

**MATERIAL:**  
Stainless Steel

#### FEATURES:

- Doors are single acting
- Non-handed
- Slide track design
- Recommended for high traffic, heavy abuse installations
- Heavy shock absorber spring provides 5-7° compression before dead stop
- On/off knob on hold open models
- Complete screw packet with thru-bolts for door, wood and machine screws for frame
- Torx® screws optional for security applications
- Durable slider cam and shock block
- 110° maximum opening
- 1 3/4" minimum door thickness
- 1 3/16" square channel
- Stop function UL listed for fire door assemblies
- For pull side mounting or flush mounting on push side or for rabbeted push side use angle jamb bracket adapter JB900LH or JB900RH

#### FASTENERS:

Jamb: 1/4"-20 x 3/4" Flat Head Machine Screws or #14 x 1 1/2" Flat Head Wood Screws

Door: 5/16"-18 x 2" Flat Head Machine Screws and 1/2" dia. Sex Bolt

#### OPTIONS:

- Hold Open
- Butts/Offset
- Pivots 33 1/16" - 38"



### AVAILABLE FINISHES:

- US32D/630
- US10BE

### WEIGHT:

4.5 lbs.

### ANSI A156.8:

C02541

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
www.rockwoodmfg.com  
1 800 458 2424

Copyright © 2019-2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.