



CL1 Series

Grade-1, heavy-duty
cylindrical lever locks



Specifications

Chassis	Steel, zinc dichromated for corrosion resistance with precision cast steel retractor
Trim	4-3/4" zinc die-cast levers, 3-1/2" wrought brass roses
Clutch Lever	Free turning lever in locked position without retracting latch for vandal resistance
Handing	Non-handed, completely reversible
Backset	2-3/4" standard
Latch	1/2" throw spring latch or deadlatch, 1-1/8" x 2-1/4" faceplate
Strike	4-7/8" x 1-1/4" ASA/ANSI strike with curved lip, optional t-strike or full lip strike
Cylinder	6-pin conventional, C keyway, keyed different, with 2 keys (keyed functions)
Thru-bolts	Fixed thru-bolts for added strength
Fasteners	Combination screws for wood or metal doors & frames
Door Prep	ANSI A115.2 - 2-1/8" crossbore with (2) 3/8" thru-bolt holes
Door Thickness	Factory set for 1-3/4" - can be adjusted to fit 1-3/8" thick doors
Applications	Exterior or interior doors in commercial, institutional, and industrial buildings
Finishes	US26D/626 satin chrome
Warranty	Limited lifetime warranty

Code compliance

ANSI/BHMA	Meets ANSI/BHMA A156.2, Series 4000, Grade 1 standards, exceeds 1,000,000 cycles
UL/cUL	UL listed for "A" label 3 hour fire-rated doors
ADA	Meets ADA and ANSI A117.1 accessibility codes
CA Fire	Meets California code for 1/2" lever return to door face





CL1 Series

Grade-1, heavy-duty
cylindrical lever locks



Non-keyed functions



CL1-75
ANSI F75
Passage

Both levers always unlocked and
always free for immediate egress.



CL1-76
ANSI F76
Privacy

Inside lever locked by push button
and unlocked by emergency release
outside, rotating inside lever or
closing door. Inside lever always free
for immediate egress.

Keyed functions



CL1-82
ANSI F109
Entry / Office

Turn / push button locking: Pushing
and turning inside button locks
outside lever, requiring use of key
until button is manually unlocked.
Pushing button locks outside lever
until unlocked with key or inside
lever is turned. Inside lever always
free for immediate egress.



CL1-84
ANSI F84
Classroom

Outside lever is locked and unlocked
by key. Inside lever is always
unlocked and always free for
immediate egress.



CL1-86
ANSI F86
Storeroom

Outside lever is always locked.
Entrance by key only. Inside lever is
always unlocked and always free for
immediate egress.