



## TDE-2000R Series

Grade-1, rim exit devices



### Specifications

---

Construction	Roll formed steel mechanism case, steel cover plate, chassis, center case cover, push pad, and end cap (painted finish)
Handing	Non-handed, completely reversible
Latchbolt	Deadlocking latchbolt with 5/8" projection, stainless steel
Strike	Roller strike with 5/8" projection, includes 1/8" shim plate
Dogging	5/32" hex key dogging standard on panic exit hardware (no dogging on 'F' model)
Lengths	3ft (for 2'4" to 3'0" wide doors and 4ft (for 3'4" to 4'0" wide doors)
Center Case	6" height x 2-15/16" wide x 2-1/2" thick - 4" minimum stile required
Projections	2-1/2" neutral or undogged, 1-13/16" depressed or dogged
Fasteners	Wood, machine & self tapping machine screws, 'F' model includes thru-bolts
Trim	Escutcheon lever, key-in-lever, and pull plate trim options
Accessories	ASA strike and latch fillers included, shim kits and other accessories available
Applications	Exterior or interior doors in commercial and industrial buildings
Finishes	AL/SP28 aluminum, BLK/622 flat black
Warranty	Limited lifetime warranty

### Code compliance

---

ANSI/BHMA	Meets ANSI/BHMA A156.3 Grade 1 standards
UL/cUL	UL listed panic hardware, 'F' model UL listed for "A" label 3 hour fire doors
ADA	Meets ADA and ANSI A117.1 accessibility codes with lever trim
CA Fire	Lever trim meets California code for 1/2" lever return to door face

