## VISION FRAME WITH 12 GAUGE SECURITY GRILLES: VLF-SG™

## Security Vision Frame With Security Grille Each Side of Glass

## **SPECIFICATIONS:**

Material:	18 gauge CRS frame. Min size 4" x 4", Max 60" x 72". See Fire Rating Below.			
Grille:	12 gauge CRS with 13/16" square openings 1" on center.			
Construction:	Mitered and welded corners, countersunk mounting holes both sides, security grille welded to frame.			
Powder Coat Finishes:	(B) Mineral Bronze (standard color)(BK) Black(FBK) Flat Black(W) White(SB) SC Beige(SI) Silver(BRA) Brass(S) Sand(AB) AMS Beige(G) Gray View Colors Online			
Door:	For 1-3/4" door. <b>Door cutout = order size.</b>			
Fasteners:	#8 x 32 Phillips head thru bolts with blank head one side to match finish.			
Glass:	3/16" - 1/4" glazing to be ordered separately from <b>Glazing Section</b> of catalog. Use fire rated glazing with Warnock Hersey (WHI) or UL classification markings for fire rated applications. Visible light is 1" under rough opening size. <u>Glass size is 1/4" under order size.</u> Fire-Rated Air Louvers Glazing to fit this vision frame: WS, KFRF, PPF			
Fire-Rating, Testing & Listings:	When installed in properly rated and approved door, ratings up to 90 minutes can be achieved, depending on the glazing used. See glazing ratings for max exposed area. Tested and Listed for UL 10C and Criteria of UBC 7-2 Positive Pressure. See detailed installation instructions.			

## **OPTIONS AT ADDITIONAL COST:**

Order Format: VLF-SG





UBC 7-2 Installation:	Additional intumescent tape for <b>Positive Pressure UL10C</b> .  See detailed installation instructions.		
Finishes & Materials:	(G) Galvanneal Sheet for Exterior Applications. (E) Electro Zinc Plating for Maximum Corrosion Resistance.		
Fasteners:	Torx Other:		
Privacy Screen:	Add the Velo Privacy Screen to This Vision Lite—See Web Page for Details		
Custom:	PAK, leadlined or special orders—contact customer service.		

Option G,E

W

			u						
VLF-SG									
7/-/-									
	ك								
			- 1						
<u></u>			Ī						
- 1	SS.								
VISIBLE LITE = 1" UNDER ORDER SIZE —	GLAZING SPACE IS GLASS THICKNESS PLUS 3/8"	SECURITY GRILLE	 						
RDEF	ING S S THI PLUS	SECURITY GRILLE	ORDER SIZE = DOOR CUT OUT						
ER 0	GLAZ GLAS	SEC GIR	OR CL						
QND	=		= DO(						
Ш    <del> </del>		IS 1/4,	SIZE						
ELITI		SIZE	DER						
ISIBLI		ASS	- OR						
>									
+	_								
1 1/4	<sub>."</sub>	<u> </u>	_ 🔻						
1									
	1	1							
		*							

Example: VLFSG 1212 W

Interpretation of Fire and Building Codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

Н

Color

AIR	Distributor:		Width:	x Height:			
AIR	Architect:		Quantity:				
ACTIVAR <sub>INC.</sub>	Contractor:		Model:				
© 2019 Activar Construction Products Group, Inc.	Project:		Date:	Version: ALPDS1901			
800-554-6077 Quo	TES@ACTIVARCPG.COM	ORDERS@ACTIVARCPG.COM	SALES@AC	TIVARCPG.COM			
VISIT <u>www.activarcpg.com</u> for the most updated product information before ordering							
MFG: COMMERCE CA, BLOOMINGTON, MN • WAREHOUSES: LANCASTER PA, ATLANTA GA, CHICAGO IL, SEATTLE WA, FORT MYERS FL, DALLAS TX, FARGO ND, OMAHA NE							