Architectural

ACCESS DOOR

The Babcock-Davis Architectural Access Door is built with the architect in mind. Constructed with an industry-standard steel door, the updated design further improves on strength and aesthetics.

FEATURES

ANTI-FLEX FRAME Screws are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.

PAINLESS INSTALLATION When mounting screws are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.

OPTIONAL STAINLESS STEEL The spot free design on the face of the door gives an aesthetically pleasing appearance.



DETAILS

DOOR

- BNT/BNW: 16 gauge Steel
- BNP: 14 gauge Steel
- 16 gauge Type 304 Stainless Steel

FRAME

- 16 gauge Steel
- 16 gauge Type 304 Stainless Steel

SI7F

- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

INSTALLATION Ceiling or Wall

FLANGE 1 inch Exposed, Drywall Bead or Plaster Bead

HINGE Concealed Spring Button

PAN DEPTH 1/2 inch

FINISH White Powder Coat (Steel) or #4 Satin (Stainless Steel)

MATERIALS



White Powder Coat



#4 Satin Stainless Steel

FLANGES







Drywall Bead



Plaster Bead

LATCHES



Screwdriver Cam Latch



Key Operated Cam Lock



Mortise Lock Prep



Knurled Knob

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	Х	LENGTH	OPTIONS	
BN				x			
	T 1 inch Flange	c Screwdriver Cam	Standard	Standard Sizes (W x L)		В	Galvannealed
	W Drywall Bead	Latch	6" x 6" 8" x 8"	16" x 20" 18" x 18"		D14	14 gauge Steel Door
	P Plaster Bead	L Key operated Cam Lock	10" x 10" 12" x 12"	18" x 24"		G	Gasketing
		M Mortise Lock	12" x 18"	22" x 22"	32" x 32"	L	Louvered Door
		(1-1/8") Prep	12" x 24" 14" x 14"	22" x 30" 24" x 24"		М	Masonry Anchors
		N Knurled Knob	16" x 16"	24" x 30"		S	Type 304 Stainless Steel

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.